

COMBINATION LOCK (4)

Operating Features

SAFE & VAULT MANUFACTURERS


OPERATING CHANGING INSTRUCTIONS

Before operating the lock or changing the combination, **READ THESE INSTRUCTIONS THOROUGHLY**

At the top of the dial ring (at 12 O'Clock) an index is provided for normal dialing and opening. At the side of the opening index (at 11 O'Clock) a changing index is provided for use only when setting a new combination.

This is a precision lock, therefore, extreme care must be used to align the combination numbers with the index. (No tolerance allowed.)

Turn the dial slowly and steadily. If, after turning the correct number of revolutions, any number is tuened beyond the index, the entire series of combination numbers must be re-dialed. **DO NOT TURN BACK TO REGAIN A PROPER ALIGNMENT WITH THE NUMBERS.** Each time a selected number is aligned with the opening index, a revolution is counted.



TO OPEN:

TO UNLOCK ON A 4 NUMBER COMBINATION - For Example "10-20-30-40" see figures 1-4 Below

1. Turn dial to the **RIGHT** stopping when "10" is aligned with the opening index the FIFTH time.
2. Turn dial to the **LEFT** stopping when "20" is aligned with the opening index, the FOURTH time.
3. Turn dial to the **RIGHT** stopping when "30" is aligned with the opening index the THIRD time.
4. Turn dial to the **LEFT** stopping when "40" is aligned with the opening index, the SECOND time.
5. Turn dial firmly to the **RIGHT** until the dial comes to a dead stop.



TO LOCK:

Turn the dial to the **LEFT** at least five full revolutions.



TO CHANGE NUMBER:

Make up a new combination, selecting 4 sets of numbers of your own choosing

DO NOT use numbers between 0 and 20 for your last number


Using the changing index, dial the whole of the **existing** combination (assuming 10-20-30-40) as follows:

1. Turn the dial to the **RIGHT** stopping when 10 is aligned with the changing index the FIFTH time.
2. Turn dial to the **LEFT** stopping when 20 is aligned with the changing index the FOURTH time.
3. Turn the dial to the **RIGHT** stopping when 30 is aligned with the changing index the THIRD time.
4. Turn the dial to the **LEFT** stopping when 40 is aligned with the changing index the SECOND time.

The lock is now ready to insert the change key into the hole on the back of lock.

Ensure the change key is properly inserted as per Fig. 1. Turn change key a quarter of a turn left as per Fig. 2.

Figure 1.




Wing on Key passes thru slot in lock plate.

Figure 2.



Figure 3.



Using the changing index, dial the whole of the **new** combination (assuming 10-20-30) as follows:

1. Turn the dial to the **RIGHT** stopping when 10 is aligned with the changing index the FIFTH time.
2. Turn dial to the **LEFT** stopping when 20 is aligned with the changing index the FOURTH time.
3. Turn dial to the **RIGHT** stopping when 30 is aligned with the changing index the THIRD time.
4. Turn the dial to the **LEFT** stopping when 40 is aligned with the changing index the SECOND time.

Turn the change key right as per Fig. 3. and remove key. Dial the new combination 10-20-30 the opening index P.T.O



CAUTION

BEFORE CLOSING THE UNIT, try the new combination several times, using the opening index.

WARNING: NEVER INSERT THE CHANGING KEY IN THE LOCK WHEN THE COVER IS REMOVED. ALWAYS BE CERTAIN THAT THE WING OF THE CHANGING KEY IS ENTIRELY WITHIN THE LOCK (Figure 2) BEFORE TURNING THE KEY.

IF AN ERROR HAS BEEN MADE IN SETTING A NEW COMBINATION, we suggest that an accredited locksmith be called.



Call us for more info (02) 9547 1488

CMI SAFE CO AUSTRALASIA PTY LTD
SINCE 1946 AUSTRALIA'S LEADING SAFE & VAULT MANUFACTURER



244 West Street, Carlton, NSW 2218



www.cmisafe.com.au



sales@cmisafe.com.au



Agents in all major Cities throughout Australia